

**HOTPOOL INSTANTANEOUS ELECTRIC WATER HEATER  
SPECIFICATION SHEET (HPI-8)**

<b>Brand Name</b>	<b>Hotpool Instant</b>
<b>Model No.</b>	<b>HPI-8</b>
Loading (kW)	8
Voltage (VAC)	220
Hertz	50
Temperature Rise (8kW)	$\Delta T = 25k @ 5l/min$
Amps.	36.4 Amp
Min. Water Flow to Operate	2.1 l/min.
Min. Water Pressure to Operate	0.1 MPa.
Working Pressure	1.0 MPa.
Testing Pressure	2 MPa.
Pre-Set Cutout Temperature	150 °C
Overheat Cutout Resettable	2 switches on coil, Manual
Type of Heating Element	Heat exchanger coil
<b>Water Container</b>	
Capacity of Water Container	n/a
Material	Copper
<b>Outer Casing</b>	
Material	PC
Colour	White base, white front cover
Finish	High Gloss
Shape	Rectangular
<b>Dimension</b>	
Height	255 mm
Width	195 mm
Depth	95 mm
Net Weight	2.5 kg
Ingress Protection Rating	IP 24
Country of Origin	Germany
Standard to Which Compliance Is Claimed	IEC 60335-1 / IEC 60335-2-35 / IEC62233 Hong Kong Electrical Products (Safety) Regulation
Water Connection	BSP 1/2"



# HPI-8

即熱式電熱水器  
ELECTRIC INSTANTANEOUS  
WATER HEATER

Sole Agent:



電寶實業有限公司 Hotpool Industries Limited

香港葵涌葵喜街13-29號 永恆工業大廈16樓7-12室

Flat 7-12,16/F., Wing Hang Ind. Bldg.,

13-29 Kwai Hei St., Kwai Chung, H.K.

Tel: (852) 3622 3800 Fax: (852) 3622 3820

陳列室 Showroom: 香港旺角上海街665號地下


Ground Floor, 665 Shanghai St., Mongkok, H.K.

Specifications subject to change without prior notice, some illustrations indicate overseas models and may not be available locally.

本文所載資料、圖片及產品規格，只供參考，如有更改，恕不另行通知。



MADE IN GERMANY



100%德國製造



# 電寶即熱

## HOTPOOL INSTANT

### HPI-8 即熱式電熱水器

**電寶即熱 HPI-8** 體積迷你小巧，安裝簡易方便。360°全方位安裝專為狹小空間而設計，最適合廚房或洗手盆應用。全機德國製造並以熱交換系統的獨特設計加熱用水，有效防止因乾燒而損壞發熱芯。只需極低入水流量就能即時啟動，用水即開即熱節能省時。加上水電分離安全設計適合用於任何水質，使**HPI-8**更為耐用，安全。

### HPI-8 ELECTRIC INSTANTANEOUS WATER HEATER

**HOTPOOL INSTANT HPI-8** is small in size and all angle installation design, easily to be installed particularly for narrow spaces such as under sink or wash basin. 100% made in Germany and equipped with the unique heat exchange system which prevents damage caused by running dry. Heater can be activated with very low water flow rate. It means that you can enjoy hot water immediately with energy efficiency.

符合香港《電氣產品（安全）規例》

Comply with the Hong Kong Electrical Products (Safety) Regulation

